

OGSA™ WSRF Basic Profile 1.0

Status of This Memo

- 5 This memo provides a recommendation to the Grid community on how to write normative OGSA services. The intention of this profile is to describe precisely the requirements placed on implementations of such services to ensure interoperability. Distribution is unlimited.

Copyright Notice

- 10 Copyright © Global Grid Forum (2005). All Rights Reserved.

Trademarks

OGSA is a trademark of the Global Grid Forum.

Abstract

- 15 The growing number of Web services specifications makes it important to understand and define the interaction and use of these specifications to ensure interoperability. Within the context of basic Web services, it has proved useful to define normative profiles that provide guidance on issues of interoperability. One such profile is the WS-I Basic Profile 1.1 [**WS-I BP 1.1**]. Guided by the principle of interoperation through conformance specification and operating in the wider technical domain of distributed system management and grid computing, we define here the
20 OGSA WSRF Basic Profile 1.0, the first of a set of normative profiles addressing issues relating to distributed resource management and grid computing.

- The OGSA WSRF Basic Profile 1.0 described in this document is an *OGSA Recommended Profile as Proposed Recommendation* as defined in the OGSA Profile Definition [**OGSA Profile Definition**]. The OGSA WSRF Basic Profile 1.0 describes uses of widely accepted specifications
25 that have been found to enable interoperability. The specifications considered in this profile are specifically those associated with the addressing, modeling, and management of state: WS-Addressing [**WS-Addressing**], WS-ResourceProperties [**WS-ResourceProperties**], WS-ResourceLifetime [**WS-ResourceLifetime**], WS-BaseNotification [**WS-BaseNotification**], and WS-BaseFaults [**WS-BaseFaults**].

30

Contents

	OGSA WSRF Basic Profile 1.0	1
	Abstract	1
35	1 Introduction	4
	1.1 Profile Overview	4
	1.2 Relationships to Other Profiles.....	4
	1.3 Notational Conventions.....	5
	1.4 Profile Identification and Versioning	6
40	2 Profile Conformance	6
	2.1 Conformance Targets	6
	2.2 Claiming Conformance	6
	3 Addressing	7
	3.1 Endpoint Reference	7
45	4 Resource Property	7
	4.1 Resource Property Definition	7
	4.2 Get Multiple Resource Properties	9
	4.3 Query Resource Properties	10
	4.4 Resource Property Change Notification	10
50	5 Resource Lifetime	11
	5.1 Immediate Resource Termination.....	11
	5.2 Scheduled Resource Termination.....	11
	6 Base Notification	12
	6.1 Notification Producer.....	12
55	7 Base Faults	13
	7.1 Base Faults.....	13
	8 Security	13
	Author Information.....	14
	Contributors	14
60	Acknowledgements	14
	Intellectual Property Statement.....	14
	Full Copyright Notice.....	14
	Normative References	15
	Non-Normative References	16
65	Appendix A. Referenced Specifications.....	17
	Appendix B. Extensibility Points.....	18
	Appendix C. OGSA Resource Properties – Normative	19

70

C.1. ResourcePropertyNames Resource Property Element Definition.....	19
C.2. FinalWSResourceInterface Resource Property Element Definition	19
C.3. WS ResourceInterfaces Resource Property Element Definition	19
C.4. Resource Endpoint Reference Resource Property Element Definition	20
Appendix D. OGSA WSRF Basic Profile Schema	21
Appendix E. Referenced Specification Status and Adoption Level Classification	23

75

75 1 Introduction

This document defines the OGSA WSRF Basic Profile 1.0 (hereafter, "the Profile"), consisting of a set of de facto, institutional or evolving institutional Web services specifications, along with clarifications, refinements, interpretations and amplifications of those specifications that promote interoperability among implementations of those specifications.

80 Section 1 introduces the Profile, and explains its relationships to other profiles.

Section 2, "Profile Conformance," explains what it means to be conformant to the Profile.

Each subsequent section addresses a component of the Profile, and consists of two parts: an overview detailing the component specifications and their extensibility points, followed by subsections that address individual parts of the component specifications. Note that there is no
85 relationship between the section numbers in this document and those in the referenced specifications.

1.1 Profile Overview

The Profile is intended for use when implementing services that are concerned with distributed resource management, grid computing, or other purposes that involve the modeling and
90 management of stateful entities. These services frequently can benefit from the use of interfaces and behaviors defined in the WS-Addressing, WS-Resource Framework, and WS-Notification families of specifications. A service implementation that uses those specifications in a manner conformant with the Profile may be said to be an "implementation of the OGSA WSRF Basic Profile 1.0" or, informally, to be an "OGSA service." (See section 2.3, "OGSA Branding", of the
95 OGSA Roadmap document [**OGSA Roadmap**].)

The primary issues addressed in the profile are as follows:

- *Addressing*. The Profile mandates the use of WS-Addressing endpoint references and places some constraints on their structure, thus enabling interoperable addressing.
- 100 • *Resource Properties*. The Profile mandates that a resource support certain resource properties, thus facilitating introspection, and also mandates support for certain operations that are optional in the WS-ResourceProperties specification. Both sets of requirements facilitate interoperability by allowing a client to make more assumptions about a service's interfaces.
- 105 • *Resource Lifetime*. The Profile mandates the use of the ImmediateResourceTermination and ScheduledResourceTermination portTypes and their associated operations and properties for immediate and scheduled termination of resources.
- *Base Notification*. The Profile mandates the use of the NotificationProducer portType and its associated operations and properties to provide notification using a publish/subscribe pattern.
- 110 • *Base Faults*. The Profile mandates the use of the fault structure specified in WS-BaseFaults and, where applicable, extends the fault structure.

This is not a complete list; see the sections that follow for details.

1.2 Relationships to Other Profiles

This Profile extends the WS-I Basic Profile 1.1 [**WS-I BP 1.1**]. All requirements except for section
115 5 "Service Publication and Discovery" specified in WS-I BP 1.1 pertain to this Profile. There may be additional profiles in the future that will include discovery functions. This Profile mandates composition with an OGSA Basic Security profile as described in Section 8.

1.3 Notational Conventions

120 The keywords "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in RFC2119 [RFC2119].

Normative statements of requirements in the Profile are presented in the manner detailed in the WS-I Basic Profile 1.1 Conformance Requirements section.

125 Both requirement statements and extensibility statements can be considered namespace-qualified.

This specification uses a number of namespace prefixes throughout; their associated URIs are listed below. Note that the choice of any namespace prefix is arbitrary and not semantically significant.

Table 1 Namespaces used by OGSA WSRF Basic Profile 1.0

Prefix	Namespace
ogsa-bp	http://www.ggf.org/namespaces/OGSABasicProfile-1.0.xsd
soap	http://schemas.xmlsoap.org/soap/envelope
wSDL	http://schemas.xmlsoap.org/wSDL
xsd	http://www.w3.org/2001/XMLSchema
xsi	http://www.w3.org/2001/XMLSchema-instance
wsa	http://www.w3.org/2005/03/addressing
wsi	http://ws-i.org/schemas/conformanceClaim
wsrf-rp	http://docs.oasis-open.org/wsrf/rp-1
wsrf-rpw	http://docs.oasis-open.org/wsrf/rpw-1
wsrf-rl	http://docs.oasis-open.org/wsrf/rl-1
wsrf-rlw	http://docs.oasis-open.org/wsrf/rlw-1
wsrf-bf	http://docs.oasis-open.org/wsrf/bf-1
wsnt	http://docs.oasis-open.org/wsn/b-1
wsntw	http://docs.oasis-open.org/wsn/bw-1

130

This Profile uses a number of special terms to refer to referenced specifications.

- **WS-Addressing** – Web Services Addressing 1.0 - Core [WS-Addressing]

- **WS-ResourceProperties** – Web Services Resource Properties 1.2 [**WS-ResourceProperties**]
- 135 • **WS-ResourceLifetime** – Web Services Resource Lifetime 1.2 [**WS-ResourceLifetime**]
- **WS-BaseNotification** – Web Services Base Notification 1.3 [**WS-BaseNotification**]
- **WS-BaseFaults** – Web Services Base Faults 1.2 [**WS-BaseFaults**]
- **SchemaCentricCanonicalization** – Schema Centric XML Canonicalization Version 1.0 [**SchemaCentric-XML-C14N**]

140 1.4 Profile Identification and Versioning

Profile identification and versioning uses the style described in WS-I Basic Profile 1.1 and abides by the normative descriptions contained therein. The name of this Profile is "OGSA WSRF Basic Profile" and version number is "1.0."

2 Profile Conformance

145 Conformance to the Profile is defined normatively in WS-I Basic Profile 1.1. This Profile abides by those definitions.

2.1 Conformance Targets

150 Since the Profile is an extension of the WS-I Basic Profile 1.1 it may place further restrictions on conformance targets defined in WS-I Basic Profile 1.1. Further, this specification defines an additional conformance target called ENDPOINTREFERENCE.

The following conformance targets are used in the Profile:

- **ENDPOINTREFERENCE** – the serialization of the `wsa:EndpointReference` element and its content
- 155 • **ENVELOPE** – the serialization of the `soap:Envelope` element and its content (from WS-I Basic Profile 1.1)
- **DESCRIPTION** – descriptions of types, messages, interfaces and their concrete protocol and data format bindings, and the network access points associated with Web services (e.g., WSDL descriptions) (from WS-I Basic Profile 1.1)
- 160 • **INSTANCE** – software that implements a `wsdl:port` (from WS-I Basic Profile 1.1, without "bindingTemplate" from the namespace `urn:uddi-org:api_v2`)
- **CONSUMER** – software that invokes an INSTANCE (from WS-I Basic Profile 1.1)
- **SENDER** – software that generates a particular message according to the protocol(s) associated with that message (from WS-I Basic Profile 1.1)
- 165 • **RECEIVER** – software that consumes a message according to the protocol(s) associated with that message (e.g., SOAP processors) (from WS-I Basic Profile 1.1)

2.2 Claiming Conformance

Claims of conformance to the Profile and the attachments mechanisms are the same as normatively described in WS-I Basic Profile 1.1.

170 The conformance claim URI for this Profile is <http://www.ggf.org/namespaces/OGSABasicProfile-1.0>.

3 Addressing

This section of the Profile incorporates the following specification by reference, and defines extensibility points within it:

- 175 • Web Services Addressing 1.0 - Core [**WS-Addressing**]
Extensibility points:
 - **E0301 – WS-Addressing Extensibility** – WS-Addressing allows extensibility elements for the wsa:EndpointReference element.
 - **E0302 – WS-Addressing Metadata Extensibility** – WS-Addressing allows extensibility elements for metadata as children of the wsa:Metadata element.
 - 180 ○ **E0303 – WS-Addressing Reference Parameters Extensibility** – WS-Addressing allows extensibility elements for Reference Parameters as children of the wsa:ReferenceParameters element.

3.1 Endpoint Reference

The following specification (or sections thereof) is referred to in this section of the Profile:

- 185 • Web Services Addressing, Section 2 [**WS-Addressing**]

WS-Addressing defines the endpoint reference structure for referencing services and WS-Resources. The Profile mandates the use of that structure, and places the following constraints on its use:

3.1.1 Endpoint Reference Structure

- 190 **R0311** *An ENDPOINTREFERENCE MUST conform to the structure specified in Web Services Addressing Section 2, "Endpoint References."*

4 Resource Property

This section of the Profile incorporates the following specification by reference, and defines extensibility points within it:

- 195 • Web Services Resource Properties 1.2 [**WS-ResourceProperties**]
Extensibility points:
 - **E0401 – Resource Property Document Extensibility** – Any resource property document MAY include standard XML extensibility through the use of xsd:any.
 - 200 ○ **E0402 – Resource Property Element Extensibility** – Any resource property element MAY include standard XML extensibility through the use of xsd:any.
 - **E0403 – QueryExpression Extensibility** – The Query Expression supported by the QueryResourceProperties message exchange is defined as open content (xsd:any).

4.1 Resource Property Definition

- 205 WS-ResourceProperties does not define any resource property elements. In contrast, the Profile requires the resource property elements listed below for introspection purposes. The Profile mandates the use of these resource property elements, and places the following constraints on their use.

4.1.1 *ResourcePropertyNames Resource Property Element Description*

210 Each instance of a WS-Resource is required to provide the ability to retrieve, through the
GetResourceProperty or GetMultipleResourceProperties message exchange pattern, a list of all
resource property element QNames that it contains. (See Appendix C.)

215 **R0411** A DESCRIPTION MUST contain in the Resource Property Document schema, as
referred to by the *wsrf-rp:ResourceProperties* attribute on the *portType*, a
Resource Property Element *ogsa-bp:ResourcePropertyNames* as defined in
the schema <http://www.ggf.org/namespaces/OGSABasicProfile-1.0.xsd> (see
Appendix D).

220 **R0412** A RECEIVER MUST respond to a *wsrf-rp:GetResourceProperty*
request where the child of the *wsrf-rp:GetResourceProperty* is the
QName *ogsa-bp:ResourcePropertyNames* with the complete list of
the *xsd:QNames* of all Resource Property Elements contained in
the Resource Property Document at the time of receipt of the
message.

225 **R0413** A RECEIVER MUST respond to a *wsrf-rp:GetMultipleResourceProperties*
request where the child of the *wsrf-rp:GetMultipleResourceProperties*
contains the QName *ogsa-bp:ResourcePropertyNames* with the
complete list of the *xsd:QNames* of all Resource Property Elements
contained in the Resource Property Document at the time of receipt of
the message.

230 4.1.2 *FinalWSResourceInterface Resource Property Element Description*

Each instance of a WS-Resource is recommended to provide the ability to retrieve, through the
GetResourceProperty or GetMultipleResourceProperties message exchange pattern, the final
portType interface QName. (See Appendix C.)

235 **R0414** A DESCRIPTION MUST contain in the Resource Property Document schema,
as referred to by the *wsrf-rp:ResourceProperties* attribute on the *portType*,
a Resource Property Element *ogsa-bp:FinalWSResourceInterface* as
defined in the schema <http://www.ggf.org/namespaces/OGSABasicProfile-1.0.xsd> (see Appendix D).

240 **R0415** A RECEIVER SHOULD respond to a *wsrf-rp:GetResourceProperty*
request where the child of the *wsrf-rp:GetResourceProperty* is the
QName *ogsa-bp:FinalWSResourceInterface* with the *xsd:QName* of
the *wsdl:portType* associated with the endpoint to which the
message was addressed.

245 **R0416** A RECEIVER SHOULD respond to a *wsrf-rp:GetMultipleResourceProperties*
request where the child of the *wsrf-rp:GetMultipleResourceProperties*
contains the QName *ogsa-bp:FinalWSResourceInterface* with the
xsd:QName of the *wsdl:portType* associated with the endpoint to which
the message was addressed.

4.1.3 *WSResourceInterfaces Resource Property Element Description*

250 Each instance of a WS-Resource is recommended to provide the ability to retrieve, through the
GetResourceProperty or GetMultipleResourceProperties message exchange pattern, a list of all
known portTypes that were composed together to make a new portType for the *wsdl:Service/port*.
Each portType must be referenced by a QName, where the namespace of the QName is that of
the parent *wsdl:definition* (See Appendix C.)

255 **R0417** A DESCRIPTION MUST contain in the Resource Property Document
 schema, as referred to by the *wsrf-rp:ResourceProperties* attribute on the
portType, a Resource Property Element *ogsa-bp:WSResourceInterfaces*
 defined in the schema
 http://www.ggf.org/namespaces/OGSABasicProfile-1.0.xsd (see
 260 Appendix D).

R0418 A RECEIVER SHOULD respond to a *wsrf-rp:GetResourceProperty*
 request where the child of the *wsrf-rp:GetResourceProperty* is the
 QName *ogsa-bp:WSResourceInterfaces* with the complete list of
 the *xsd:QNames* of all the *wsdl:portTypes* that were composed into
 265 the endpoint to which the message was addressed.

R0419 A RECEIVER SHOULD respond to a *wsrf-rp:GetMultipleResourceProperties*
 request where the child of the *wsrf-rp:GetMultipleResourceProperties*
 contains the QName *ogsa-bp:WSResourceInterfaces* with the complete
 list of the *xsd:QNames* of all the *wsdl:portTypes* that were composed into
 270 the endpoint to which the message was addressed.

4.1.4 ResourceEndpointReference Resource Property Element Description

Each instance of a WS-Resource is recommended to provide the ability to retrieve, through the
GetResourceProperty or *GetMultipleResourceProperties* message exchange pattern, the
wsa:EndpointReference(s) for itself. (See Appendix C.)

275 **R0420** A DESCRIPTION MUST contain in the Resource Property Document schema,
 as referred to by the *wsrf-rp:ResourceProperties* attribute on the *portType*,
 a Resource Property Element *ogsa-bp:ResourceEndpointReference* as
 defined in the schema http://www.ggf.org/namespaces/OGSABasicProfile-
 1.0.xsd (see Appendix D).

280 **R0421** A RECEIVER SHOULD respond to a *wsrf-rp:GetResourceProperty*
 request where the child of the *wsrf-rp:GetResourceProperty* is the
 QName *ogsa-bp:ResourceEndpointReference* with the
wsa:EndpointReference(s) of the endpoint to which the message
 was addressed.

285 **R0422** A RECEIVER SHOULD respond to a *wsrf-rp:GetMultipleResourceProperties*
 request where the child of the *wsrf-rp:GetMultipleResourceProperties*
 contains the QName *ogsa-bp:ResourceEndpointReference* with the
wsa:EndpointReference(s) of the endpoint to which the message was
 addressed.

290 4.2 Get Multiple Resource Properties

WS-ResourceProperties defines a *portType* for retrieval of multiple resource properties. The
 Profile mandates the use of this *portType*, and places the following constraints on its use.

4.2.1 *wsrf-rpw:GetMultipleResourceProperties* Message Exchange

295 WS-ResourceProperties only requires that an instance of a WS-Resource implement the
GetResourceProperty message exchange pattern. The Profile also requires support for
GetMultipleResourceProperties message exchange pattern.

R0423 A DESCRIPTION MUST include the *wsrf-rpw:GetMultipleResourceProperties*
wsdl:operation as defined in **WS-ResourceProperties** section 5.3.

300 **R0424** *An INSTANCE MUST support the wsrf-rpw:GetMultipleResourceProperties message exchange to allow for the retrieval of multiple resource properties.*

4.3 Query Resource Properties

WS-ResourceProperties defines a portType for query and retrieval of resource properties. The Profile recommends the use of this portType, and places the following constraints on its use.

305 4.3.1 wsrf-rpw:QueryResourceProperties Message Exchange

WS-ResourceProperties only requires that an instance of a WS-Resource implement the GetResourceProperty message exchange pattern. The Profile also recommends support for the QueryResourceProperties message exchange pattern. Existing implementations of XPath 1.0 are prevalent and as such, the Profile requires support for the XPath 1.0 dialect. Further, without consistent serialization a client's ability to process the response will be hindered. The Profile recommends the use of SchemaCentricCanonicalization for serialization of the response.

R0425 *A DESCRIPTION SHOULD include the wsrf-rpw:QueryResourceProperties wsdl:operation as defined in **WS-ResourceProperties** section 5.4.*

315 **R0426** *An INSTANCE SHOULD support the wsrf-rpw:QueryResourceProperties message exchange to allow for the query and retrieval of multiple resource properties.*

R0427 *An INSTANCE MUST support the QueryExpression Dialect URI <http://www.w3.org/TR/1999/REC-xpath-19991116> on the wsrf-rpw:QueryResourceProperties message exchange.*

320 **R0428** *An INSTANCE, when presented with a resource property retrieval for the QName wsrf-rp:QueryExpressionDialect response, MUST (at least) include the URI <http://www.w3.org/TR/1999/REC-xpath-19991116>.*

325 **R0429** *A MESSAGE response for wsrf-rpw:QueryResourceProperties with the Dialect URI <http://www.w3.org/TR/1999/REC-xpath-19991116> SHOULD conform to the structure/serialization as defined in SchemaCentricCanonicalization.*

330 Note: Without standardized serialization of the XPath evaluation, it is unlikely a client will be able to process the QueryResourceProperties response successfully. The client will be left to deal with the vagaries of the XPath implementation with respect to such things as namespaces (or just their prefixes), comments, processing instructions, boolean values, defaults and a host of other information items. This is not a new problem; serialization of an XPath evaluation is a 'classical' problem introduced by XPath 1.0's lack of normative serialization specification. To address this shortcoming several specifications defining canonicalization/serialization algorithms have been developed: Canonical XML [**XML-C14N**], Exclusive XML Canonicalization [**XML-Exc-C14N**] and SchemaCentricCanonicalization. The first two specifications have well known issues that make them unsuitable for serialization (except in the most limited of use cases). SchemaCentricCanonicalization addresses these issues. For a complete discussion of the limitations of Canonical XML and Exclusive XML Canonicalization see

340 SchemaCentricCanonicalization Section 1.1.

4.4 Resource Property Change Notification

WS-ResourceProperties recommends support for resource property element change notifications for WS-Resources that support the wsntw:NotificationProducer [**WS-BaseNotification**] portType. OGSA services fundamentally rely on the ability to understand changes in other OGSA services.

345 The Profile recommends the use of the `wsrf-rp:ResourcePropertyValueChangeNotification` element and places the following constraints on its use.

4.4.1 Use of `wsntw:NotificationProducer`

350 The Profile recommends the use of the `NotificationProducer` portType and its associated operations and properties to support the resource property value change notification pattern for insertions, updates and deletions.

R0430 A DESCRIPTION SHOULD include the `wsntw:NotificationProducer` `wsdl:portType` as defined in **WS-BaseNotification** section 4.

R0431 An INSTANCE SHOULD support `wsnt:Subscribe` message exchange to allow for creation of `wsrf-rpw:ResourcePropertyValueChangeNotification`.

355 5 Resource Lifetime

This section of the Profile incorporate the following specifications by reference, and defines extensibility points within it:

- Web Services Resource Lifetime 1.2 [**WS-ResourceLifetime**] Extensibility points:
 - **E0501 – Termination Reason** – The termination reason in the `TerminationNotification` message type allows for open content (`xsd:any`).

360

5.1 Immediate Resource Termination

WS-ResourceLifetime defines a portType for immediate termination of a WS-Resource. The Profile mandates the use of this portType for explicit destruction of resources created as a result of a message exchange, and places the following constraints on its use:

365 5.1.1 `wsrf-rlw:Destroy` Message Exchange

WS-ResourceLifetime does not require that an instance of a WS-Resource implement any of the message exchanges that it defines. In contrast, the Profile mandates immediate destruction capability for WS-Resource instances that are created as a result of a message exchange.

370

R0511 A DESCRIPTION SHOULD include the `wsrf-rlw:Destroy` `wsdl:operation` as defined in **WS-ResourceLifetime** section 4 to allow for the immediate destruction of a WS-Resource.

R0512 An INSTANCE that is created as a result of a message exchange MUST support the `wsrf-rlw:Destroy` message exchange to allow for the immediate destruction of a WS-Resource.

375 5.2 Scheduled Resource Termination

WS-ResourceLifetime defines a portType for scheduled termination of a WS-Resource. The Profile mandates the use of this portType to provide time-based destruction of resources created as a result of a message exchange, and places the following constraints on its use:

5.2.1 `wsrf-rlw:SetTerminationTime` Message Exchange

380 WS-ResourceLifetime does not require that an instance of a WS-Resource implement any of the message exchanges that it defines. In contrast, the Profile mandates time-based destruction capability for WS-Resource instances that are created as a result of a message exchange.

R0513 A DESCRIPTION SHOULD contain in the Resource Property Document schema, as referred to by the `wsrf-rp:ResourceProperties` attribute on

385 *the portType, a Resource Property Element wsrf-rl:CurrentTime as defined in the schema <http://docs.oasis-open.org/wsrf/rl-1>.*

R0514 A DESCRIPTION SHOULD include the wsrf-rlw:SetTerminationTime wsdl:operation as defined in WS-ResourceLifetime section 5 to allow for the scheduled destruction of a WS-Resource.

390 **R0515** An INSTANCE that is created as a result of a message exchange MUST support the wsrf-rlw:SetTerminationTime message exchange to allow for the scheduled destruction of a WS-Resource.

6 Base Notification

395 This section of the Profile incorporates the following specification by reference, and defines extensibility points within it:

- Web Services Base Notification 1.3 [**WS-BaseNotification**] Extensibility points:
 - **E0601 – Subscribe Topic Expression** – The topic expression in the wsnt:Subscribe is open content (xsd:any).

6.1 Notification Producer

400 The Profile mandates the use of this portType for client-controlled notifications of events from resources, and places the following constraints on its use:

6.1.1 wsntw:Subscribe Message Exchange

405 The wsntw:Subscribe message exchange allows for notification messages to be sent over protocols other than Web services-based protocols. This flexibility impedes the interoperability of services that conform to the Profile. The Profile allows the use of this message exchange but places the following constraints on it:

R0611 A CONSUMER MUST NOT include the wsnt:SubscriptionPolicy/wsnt:UseRaw element in the wsntw:Subscribe request.

410 **R0612** An INSTANCE MUST support the TopicExpression Dialect URI <http://docs.oasis-open.org/wsn/2004/06/TopicExpression/Simple> for wsnt:Subscribe/wsnt:Filter/wsnt:TopicExpression@Dialect in the wsntw:Subscribe message exchange.

415 **R0613** An INSTANCE, when presented with a resource property retrieval for the QName wsnt:TopicExpressionDialect MUST include in the response (at a minimum) the URI <http://docs.oasis-open.org/wsn/2004/06/TopicExpression/Simple>.

420 **R0614** An INSTANCE that accepts the wsnt:Filter/wsnt:ProducerProperties element in the wsntw:Subscribe message exchange MUST support the Dialect from the namespace <http://www.w3.org/TR/1999/REC-xpath-19991116> as the content for the wsnt:Filter/wsnt:ProducerProperties element.

425 **R0615** An INSTANCE that accepts the wsnt:Filter/wsnt:MessageContent element in the wsntw:Subscribe message exchange MUST support the Dialect from the namespace <http://www.w3.org/TR/1999/REC-xpath-19991116> as the content for the wsnt:Filter/wsnt:MessageContent element.

6.1.2 Notification Message Exchange

Although WS-BaseNotification allows the use of raw notification, the Profile mandates the Notify message by R0611 and disallows raw notification. Therefore:

- 430 **R0616** *An INSTANCE MUST send the wsntw:Notify message to the NotificationConsumer in order to deliver one or more NotificationMessage(s).*

7 Base Faults

435 This section of the Profile incorporates the following specification by reference, and defines extensibility points within it:

- Web Services Base Faults 1.2 [**WS-BaseFaults**] Extensibility points:
 - **E0701 – Base Fault Type** – The Base Fault Type includes open content (xsd:any) as the last child element in sequence.

7.1 Base Faults

440 WS-BaseFaults defines the fault structure that WS-Resources use for faults that are generated by the WS-Resource. The Profile mandates the use of that structure, and places the following constraints on its use:

7.1.1 BaseFault Structure

- 445 **R0711** *A MESSAGE for a fault from a WS-Resource MUST conform to the structure specified in Web Services Base Faults Section 2, "Base Fault Type."*

7.1.2 BaseFault Extension

450 WS-BaseFaults use extension as the mechanism for 'subtyping' faults. Unfortunately, if an extension of the base introduces a new element the extension then violates the Unique Particle Attribution constraint (see <http://www.w3.org/TR/xmlschema-1/#cos-nonambig>) [**XML-Schema**]. This means that the schema component will not validate because the sequence is non-deterministic. The Profile places the following constraints on extension:

- R0712** *A DESCRIPTION for an extension of a wsrf-bf:BaseFaultType MUST NOT introduce any child elements to the sequence.*

455 8 Security

The Profile does not address security requirements directly; Grid infrastructure and environmental security requirements must be profiled in separate documents. The Profile mandates the composition with an OGSA Basic Security profile that exposes an OGSA Basic Security conformance claim along with the OGSA Security conformance claim. For instance, an OGSA anonymous channel would expose two claims, one for OGSA Basic Security conformance and one for the anonymous channel conformance.

8.1.1 OGSA Basic Security Profile Conformance Claim

465 One of the primary aspects of the OGSA security architecture is the ability for a service requester to discover the security capabilities of the service. In order to accomplish this, the Profile introduces a requirement for exposure of a well known conformance claim for all OGSA Basic Security profiles. The Profile places the following constraints on the conformance claim:

R0811 A DESCRIPTION MUST have attached to the `wsdl:portType` a `wsdl:claim` with the URI `"http://www.ggf.org/namespaces/OGSABasicSecurity-1.0"`.

470

Author Information

Ian Foster
Math & Computer Science Division
Argonne National Laboratory
Argonne, IL 60439
Email: <foster@mcs.anl.gov>

475

Tom Maguire
IBM
2455 South Road
Poughkeepsie, NY 10509
Email: <tmaguire@us.ibm.com>

480

Dr. David Snelling
Fujitsu Laboratories of Europe
Hayes Park Central
Hayes End Road
Hayes, Middlesex UB4 8FE
Email: <d.snelling@fle.fujitsu.com>

485

Contributors

We gratefully acknowledge the contributions made to this specification by Abdeslem Djaoui, Hiro Kishimoto, Sam Meder, Takuya Mori, Andreas Savva, Frank Siebenlist, Jem Treadwell, and Latha Srinivasan.

490

Acknowledgements

We are grateful to numerous colleagues for discussions on the topics covered in this document, in particular (in alphabetical order, with apologies to anybody we've missed) Michael Behrens, Dave Berry, Andrew Grimshaw, Marty Humphrey, Vivian Li, Mark McKeown, Mark Morgan, Steven Newhouse, Ravi Subramaniam, Steve Tuecke, Jay Unger, Pete Ziu.

495

Intellectual Property Statement

The GGF takes no position regarding the validity or scope of any intellectual property or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; neither does it represent that it has made any effort to identify any such rights. Copies of claims of rights made available for publication and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this specification can be obtained from the GGF Secretariat.

500

The GGF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights which may cover technology that may be required to practice this recommendation. Please address the information to the GGF Executive Director.

505

Full Copyright Notice

Copyright (C) Global Grid Forum (2005). All Rights Reserved.

510 This document and translations of it may be copied and furnished to others, and derivative works
 that comment on or otherwise explain it or assist in its implementation may be prepared, copied,
 published and distributed, in whole or in part, without restriction of any kind, provided that the
 above copyright notice and this paragraph are included on all such copies and derivative works.
 515 However, this document itself may not be modified in any way, such as by removing the copyright
 notice or references to the GGF or other organizations, except as needed for the purpose of
 developing Grid Recommendations in which case the procedures for copyrights defined in the
 GGF Document process must be followed, or as required to translate it into languages other than
 English.

520 The limited permissions granted above are perpetual and will not be revoked by the GGF or its
 successors or assigns.

This document and the information contained herein is provided on an "AS IS" basis and THE
 GLOBAL GRID FORUM DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING
 BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN
 WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY
 525 OR FITNESS FOR A PARTICULAR PURPOSE."

Normative References

- **[SchemaCentric-XML-C14N]** B. Atkinson, S. Aissi, M. Hondo (ed.), Schema Centric XML Canonicalization, OASIS Committee Specification, 10 July 2002.
<http://www.uddi.org/pubs/SchemaCentricCanonicalization-20020710.htm>
- 530 • **[RFC2119]** S. Bradner (ed.) Key words for use in RFCs to Indicate Requirement Levels, The Internet Engineering Task Force Best Current Practice, March 1997.
<http://www.ietf.org/rfc/rfc2119>
- **[WS-Addressing]** D. Box and F. Curbera (ed.) Web Services Addressing 1.0 – Core (WS-Addressing), W3C Last Call, 31 March 2005. <http://www.w3.org/TR/2005/WD-ws-addr-core-20050331>
- 535 • **[WS-BaseFaults]** S. Tuecke, L. Liu and S. Meder (ed.) Web Services Base Faults 1.2 (WS-BaseFaults), OASIS Public Review Draft 01. 13 June 2005. http://docs.oasis-open.org/wsrf/wsrf-ws_base_faults-1.2-spec-pr-01.pdf
- **[WS-BaseNotification]** S. Graham, D. Hull and B. Murray (ed.) Web Services Base Notification 1.3 (WS-BaseNotification), OASIS Public Review Draft 01, 07 July 2005.
http://docs.oasis-open.org/wsn/wsn-ws_base_notification-1.3-spec-pr-01.pdf
- 540 • **[WS-ResourceLifetime]** L. Srinivasan and T. Banks (ed.) Web Services Resource Lifetime 1.2 (WS-ResourceLifetime), OASIS Public Review Draft 01, 13 June 2005.
http://docs.oasis-open.org/wsrf/wsrf-ws_resource_lifetime-1.2-spec-pr-01.pdf
- 545 • **[WS-ResourceProperties]** S. Graham and J. Treadwell (ed.) Web Services Resource Properties 1.2 (WS-ResourceProperties), OASIS Public Review Draft 01, 10 June 2005.
http://docs.oasis-open.org/wsrf/wsrf-ws_resource_properties-1.2-spec-pr-01.pdf
- **[WS-I BP 1.1]** K. Ballinger, D. Ehnebuske, C. Ferris, M. Gudgin, C.K. Liu, M. Nottingham, and P. Yendluri (ed.) Basic Profile Version 1.1, Web Services Interoperability Organization Final Material, 24 August 2004. <http://www.ws-i.org/Profiles/BasicProfile-1.1.html>
- 550 • **[XML-Schema]** H. Thompson, D. Beech, M. Maloney, and N. Mendelsohn XML Schema Part 1: Structures Second Edition, W3C Recommendation 28 October 2004.
<http://www.w3.org/TR/xmlschema-1/>

555 **Non-Normative References**

- **[OGSA Profile Definition]** T. Maguire and D. Snelling OGSA Profile Definition Version 1.0, Global Grid Forum OGSA-WG, GWD-I (submitted), 27 June 2005. <http://forge.gridforum.org/projects/ogsa-wg/document/draft-ggf-ogsa-profile-definition/en/15>

- 560 • **[OGSA Roadmap]** H. Kishimoto and J. Treadwell (eds.) Defining the Grid: A Roadmap (version 1.0) for the Open Grid Services Architecture, Global Grid Forum OGSA-WG, GWD-I (submitted), 24 June 2005. <http://forge.gridforum.org/projects/ogsa-wg/document/draft-ggf-ogsa-roadmap/en/15>

- 565 • **[XML-C14N]** J. Boyer (ed.) Canonical XML W3C Recommendation, March 2001 <http://www.w3.org/TR/2001/REC-xml-c14n-20010315>
<http://www.ietf.org/rfc/rfc3076.txt>

- **[XML-Exc-C14N]** J. Boyer, D. Eastlake, and J. Reagle (ed.) Exclusive XML Canonicalization W3C Candidate Recommendation, 12 February 2002 <http://www.w3.org/TR/2002/CR-xml-exc-c14n-20020212>

570

Appendix A. Referenced Specifications

The following specifications' requirements are incorporated into the Profile by reference, except where superseded by the Profile:

- Web Services Addressing 1.0 – Core (WS-Addressing) [**WS-Addressing**]
- 575 • Web Services Base Faults 1.2 (WS-BaseFaults) [**WS-BaseFaults**]
- Web Services Base Notification 1.3 (WS-BaseNotification) [**WS-BaseNotification**]
- Web Services Resource Lifetime 1.2 (WS-ResourceLifetime) [**WS-ResourceLifetime**]
- Web Services Resource Properties 1.2 (WS-ResourceProperties) [**WS-ResourceProperties**]
- 580 • Basic Profile 1.1 [**WS-I BP 1.1**]
- Schema Centric XML Canonicalization Version 1.0 [**SchemaCentric-XML-C14N**]

Appendix B. Extensibility Points

585 This section identifies extensibility points for the Profile's component specifications. These mechanisms are out of the scope of the Profile; their use may affect interoperability, and may require private agreement between the parties to a Web service.

In Web Services Addressing [**WS-Addressing**]:

- **E0301 – WS-Addressing Extensibility** – WS-Addressing allows extensibility elements for the `wsa:EndpointReference`.
- 590 • **E0302 – WS-Addressing Metadata Extensibility** – WS-Addressing allows extensibility elements for metadata as children of the `wsa:Metadata` element.
- **E0303 – WS-Addressing Reference Parameters Extensibility** – WS-Addressing allows extensibility elements for Reference Parameters as children of the `wsa:ReferenceParameters` element.

595 In Web Services Resource Properties 1.2 [**WS-ResourceProperties**]:

- **E0401 – Resource Property Document Extensibility** – Any resource property document MAY include standard XML extensibility through the use of `xsd:any`.
- **E0402 – Resource Property Element Extensibility** – Any resource property document MAY include standard XML extensibility through the use of `xsd:any`.
- 600 • **E0403 – QueryExpression Extensibility** – The Query Expression supported by the `QueryResourceProperties` message exchange is defined as open content (`xsd:any`).

In Web Services Resource Lifetime 1.2 [**WS-ResourceLifetime**]

- **E0501 – Termination Reason** – The termination reason in the `TerminationNotification` message type allows for open content (`xsd:any`).

605 In Web Services Base Notification 1.2 [**WS-BaseNotification**]

- **E0601 – Subscribe Topic Expression** – The topic expression in the `wsnt:Subscribe` is open content (`xsd:any`).

In Web Services Base Faults 1.2 [**WS-BaseFaults**]

- 610 • **E0701 – Base Fault Type** – The Base Fault Type includes open content (`xsd:any`) as the last child element in sequence.

Appendix C. OGSA Resource Properties – Normative

C.1. ResourcePropertyNames Resource Property Element Definition

The general form of a ResourcePropertyNames resource property element is:

```
615 <ogsa-bp:ResourcePropertyNames>
    list of xsd:QNames
</ogsa-bp:ResourcePropertyNames>
```

Furthermore, this reference MUST reflect the minOccurs and maxOccurs properties as follows:

```
620 <xsd:element ref="ogsa-bp:ResourcePropertyNames"
    minOccurs="1" maxOccurs="1" />
```

This resource property element is further constrained as follows:

/ogsa-bp:ResourcePropertyNames

Contains a complete list of xsd:QNames of all Resource Property Elements defined in the Resource Property Document.

625 C.2. FinalWSResourceInterface Resource Property Element Definition

The general form of a FinalWSResourceInterface resource property element is:

```
<ogsa-bp:FinalWSResourceInterface>
    xsd:QName
</ogsa-bp:FinalWSResourceInterface>
```

630 Furthermore, this reference MUST reflect the minOccurs and maxOccurs properties as follows:

```
<xsd:element ref="ogsa-bp:FinalWSResourceInterface"
    minOccurs="0" maxOccurs="1" />
```

This resource property element is further constrained as follows:

/ogsa-bp:FinalWSResourceInterface

635 Optional element, if present, contains the xsd:QName of the most derived portType interface of the service.

C.3. WSResourceInterfaces Resource Property Element Definition

The general form of a WSResourceInterfaces resource property element is:

```
640 <ogsa-bp:WSResourceInterfaces>
    list of xsd:QNames
</ogsa-bp:WSResourceInterfaces>
```

Furthermore, this reference MUST reflect the minOccurs and maxOccurs properties as follows:

```
<xsd:element ref="ogsa-bp:WSResourceInterfaces"
    minOccurs="0" maxOccurs="1" />
```

645 This resource property element is further constrained as follows:

/ogsa-bp:WSResourceInterfaces

Optional element, if present, contains a complete list of xsd:QNames of all portType interfaces aggregated into the service.

650 C.4. Resource Endpoint Reference Resource Property Element Definition

The general form of an ogsa-bp:ResourceEndpointReference resource property element is:

```
<ogsa-bp:ResourceEndpointReference>  
  wsa:EndpointReferenceType  
</ogsa-bp:ResourceEndpointReference>
```

655 Furthermore, this reference **MUST** reflect the minOccurs and maxOccurs properties as follows:

```
<xsd:element ref="ogsa-bp:ResourceEndpointReference"  
  minOccurs="0" maxOccurs="unbounded" />
```

This resource property element is further constrained as follows:

/ogsa-bp:ResourceEndpointReference

660 Optional elements, if present, contain wsa:EndpointReference(s) by which a service is addressable.

Appendix D. OGSA WSRF Basic Profile Schema

665 This section contains the normative XML Schema definitions described in this document. The definitions in this section MUST be considered normative.

```
<?xml version="1.0" encoding="UTF-8"?>
```

```
<!--
```

670 The GGF takes no position regarding the validity or scope of any intellectual property or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; neither does it represent that it has made any effort to identify any such rights. Copies of claims of rights made available for publication and any assurances of licenses

675 to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this specification can be obtained from the GGF Secretariat.

680 The GGF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights which may cover technology that may be required to practice this recommendation. Please address the information to the GGF Executive Director.

685 Copyright (C) Global Grid Forum (2005). All Rights Reserved.

690 This document and translations of it may be copied and furnished to others, and derivative works that comment on or otherwise explain it or assist in its implementation may be prepared, copied, published and distributed, in whole or in part, without restriction of any kind, provided that the above copyright notice and this paragraph are included on all such copies and derivative works. However, this document itself may not be modified in any way, such as by removing

695 the copyright notice or references to the GGF or other organizations, except as needed for the purpose of developing Grid Recommendations in which case the procedures for copyrights defined in the GGF Document process must be followed, or as required to translate it into languages other than English.

700 The limited permissions granted above are perpetual and will not be revoked by the GGF or its successors or assigns.

705 This document and the information contained herein is provided on an "AS IS" basis and THE GLOBAL GRID FORUM DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE."

710 -->

```
<xsd:schema
  xmlns="http://www.w3.org/2001/XMLSchema"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
715  xmlns:wsa="http://www.w3.org/2005/03/addressing"
  xmlns:ogsa-bp="http://www.ggf.org/namespaces/OGSABasicProfile-
1.0.xsd"
  elementFormDefault="qualified"
  attributeFormDefault="unqualified"
720  targetNamespace="http://www.ggf.org/namespaces/OGSABasicProfile-
1.0.xsd" >

  <xsd:import
725    namespace="http://www.w3.org/2005/03/addressing"
    schemaLocation="http://www.w3.org/2005/03/addressing/" />

  <xsd:simpleType name="QNameListType">
    <xsd:list itemType="xsd:QName"/>
730  </xsd:simpleType>

  <xsd:element name="ResourcePropertyNames"
    type="ogsa-bp:QNameListType" />

  <xsd:element name="FinalWSResourceInterface"
735    type="xsd:QName" />

  <xsd:element name="WSResourceInterfaces"
    type="ogsa-bp:QNameListType" />

740  <xsd:element name="ResourceEndpointReference"
    type="wsa:EndpointReferenceType" />

</xsd:schema>
```

745

Appendix E. Referenced Specification Status and Adoption Level Classification

The classification of this Profile’s referenced specifications at the time of writing are in Table 2.

Table 2 Status of specifications referenced by OGSA WSRF Basic Profile 1.0

OGSA Referenced Specifications: OGSA WSRF Basic Profile 1.0														
August 31, 2005	Status							Adoption						Note
	De Facto	Institutional	Evolving Institutional	Draft Institutional	Consortium	Evolving Consortium	Draft	Ubiquitous	Adopted	Community	Interoperable	Implemented	Unimplemented	
Specification/Profile Name														
Specifications														
WS-Addressing 1.0		<	X									<	X	IBM, Apache implementing
WS-ResourceProperties 1.2		<	X									<	X	At public review
WS-ResourceLifetime 1.2		<	X									<	X	At public review
WS-BaseFaults 1.2		<	X									<	X	At public review
WS-BaseNotification 1.3		<	X									<	X	At public review
SchemaCentricCanonicalization			X									X		Committee Specification
Profiles														
WS-I Basic Profile 1.1		X						-	-	-	-	-	-	Final Material

Legend:

X	Specification or profile is currently at this status or adoption level
<	Specification or profile is approaching this status or adoption level
-	Status or adoption level is not applicable